

JC05 Rec'd PCT/PTO 05 OCT 2005
10/551961

DOCKET NO.: 278816US3PCT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

IN RE APPLICATION OF: Lars PERSSON

SERIAL NO.: NEW U.S. PCT APPLICATION

FILED: HERewith

INTERNATIONAL APPLICATION NO.: PCT/SE04/00584

INTERNATIONAL FILING DATE: April 15, 2004

FOR: EVAPORATOR AND HEAT EXCHANGER WITH EXTERNAL LOOP, AS WELL
AS HEAT PUMP SYSTEM AND AIR CONDITIONING SYSTEM COMPRISING SAID
EVAPORATOR OR HEAT EXCHANGER

REQUEST FOR PRIORITY UNDER 35 U.S.C. 119
AND THE INTERNATIONAL CONVENTION

Commissioner for Patents
Alexandria, Virginia 22313

Sir:

In the matter of the above-identified application for patent, notice is hereby given that
the applicant claims as priority:

COUNTRY
Sweden

APPLICATION NO
0301170-7

DAY/MONTH/YEAR
17 April 2003

Certified copies of the corresponding Convention application(s) were submitted to the
International Bureau in PCT Application No. PCT/SE04/00584. Receipt of the certified
copy(s) by the International Bureau in a timely manner under PCT Rule 17.1(a) has been
acknowledged as evidenced by the attached PCT/IB/304.

Respectfully submitted,
OBLON, SPIVAK, McCLELLAND,
MAIER & NEUSTADT, P.C.



C. Irvin McClelland
Attorney of Record
Registration No. 21,124
Surinder Sachar
Registration No. 34,423

Customer Number
22850

(703) 413-3000
Fax No. (703) 413-2220
(OSMMN 08/03)

BEST AVAILABLE COPY

PRVPATENT- OCH REGISTRERINGSVERKET
Patentavdelningen**Intyg
Certificate**

Härmed intygas att bifogade kopior överensstämmer med de handlingar som ursprungligen ingivits till Patent- och registreringsverket i nedannämnda ansökan.

This is to certify that the annexed is a true copy of the documents as originally filed with the Patent- and Registration Office in connection with the following patent application.



(71) Sökande EP Technology AB, Malmö SE
Applicant (s)

(21) Patentansökningsnummer 0301170-7
Patent application number

(86) Ingivningsdatum 2003-04-17
Date of filing

Stockholm, 2004-04-26

För Patent- och registreringsverket
For the Patent- and Registration Office

Marita Öun
Marita Öun

Avgift
Fee

PRIORITY DOCUMENT
SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH
RULE 17.1(a) OR (b)

REC'D 03 MAY 2004

WIPO PCT

**PATENT- OCH
REGISTRERINGSVERKET
SWEDEN**

Postadress/Adress
Box 5055
S-102 42 STOCKHOLM

Telefon/Phone
+46 8 782 25 00
Vx 08-782 25 00

Telex
17978
PATOREG S

Telefax
+46 8 666 02 86
08-666 02 86

46 40 6119689

EVAPORATOR AND HEAT EXCHANGER WITH EXTERNAL LOOP

Ink t Patent- och r

7003 -04-

FIELD OF THE INVENTION

Huvudföreläsnings K

5 The present invention relates generally to an evaporator and more specifically to an evaporator equipped with drainage means for improving its efficiency and decrease the wear of a co-operating compressor. The invention also relates to a condenser to be used together with said evaporator in a heat exchanger of the plate type.

10

STATE OF THE ART

Evaporators and condensers are devices e.g. used for heat exchangers, such as e.g. slender tube heat exchangers, plate type heat exchangers, spiral heat exchangers
15 etc. In a heat exchanger according to the plate type the media circulate inside alternating plates, typically made of metal and brazed together with sealed inlets and outlets forming closed duct systems within a package of interacting, interconnected, plates in which the media circulate under heat exchange. The published patent application WO 00/03189, A1, describes such a plate type heat exchanger in more
20 detail.

Figure 1 illustrates the working principle of a conventional heat exchanger with a compressor driven evaporation process. Such a heat exchanger includes an evaporation chamber 110 in which the cooling medium absorbs heat, Q , and thereafter evaporates whereupon it is directed to a compressor 120 and then further
25 directed to a condenser chamber 130 where said medium emits heat, Q , and condenses. The medium is then fed back to the evaporation chamber 110 through an expansion valve 140. A problem for the conventional heat exchanger illustrated in fig. 1 relates to the fact that accumulated liquid in the evaporation chamber, indicated by liquid level 150 in fig. 1, will decrease the efficiency of the heat
30 exchanger, for reasons known to a person skilled in the art. A further problem is that said accumulated liquid also increases the amount of liquid leaving the chamber 110 with detrimental effects for the compressor 120, as known to a person skilled in the art.

One way to increase the efficiency of the heat exchanger illustrated in fig. 1 is to
35 provide additional heating of the medium in zone 170 and additional cooling of the medium in zone 160 in fig. 1, by means of a so called superheater/supercooler, as known to a person skilled in the art. The superheater/supercooler function will also decrease the wear of compressor 120 in fig. 1, since compressor 120 will receive a decreased amount of liquid. One problem in conventional heat exchangers is that
40 these superheaters/supercoolers are realised as external units making the heat

exchangers bulky and not always cost effective. A particular problem relating to heat exchangers of the plate type is that accumulated liquid medium in the lower parts of the evaporator will cause non uniform streaming with a decreased efficiency as a result.

5 The present invention solves or reduces the above problems.

SUMMARY OF THE INVENTION

It is an object of the present invention to solve the problems mentioned above.

10 One object of the present invention is thus to provide a more efficient evaporator.

Another object of the present invention is to decrease the wear of a compressor connected to, and co-operating with, an evaporator.

15 Still another object of the present invention is to improve the efficiency of heat exchangers in general and heat exchangers of the plate type in particular.

Still a further object of the present invention is to provide a heat exchanger of the plate type with an integrated supercooler/superheater.

20 The present invention provides an evaporator equipped with drainage means that drain accumulated liquid from the evaporator's lower parts. The drainage means include an injector and/or a pump.

The present invention also provides a superheater/supercooler in a heat exchanger of the plate type by providing interacting delimited zones in the heat exchanger's evaporator and condenser.

25 The invention is defined by the accompanying claims 1 and 6, whereas advantageous embodiments are defined by the dependent claims 2-5 and 7-14.

BRIEF DESCRIPTION OF THE DRAWINGS

30 The invention will be described in detail below, with reference to the accompanying drawings, of which:

Fig. 1 illustrates the working principle of a conventional heat exchanger;

Fig. 2 illustrates different embodiments of an evaporator used in a heat exchanger according to the present invention;

Fig. 3 illustrates an example of how a first plate side, i.e. an A' front side, of a plate type heat exchanger according to the present invention could be designed;

Fig. 4 illustrates an example of how a second plate side, i.e. a B' rear side, of a plate type heat exchanger according to the present invention could be designed.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

A problem regarding the efficiency of an evaporator is that ideally no liquid
5 medium should leave the evaporator, i.e. the liquid content of the evaporated
medium should be zero, which is hard to obtain in practise. One object of the present
invention is thus to provide a more efficient evaporator by minimising the liquid
content of the evaporated medium leaving the evaporator.

Another problem is that a higher liquid content of the evaporated medium will
10 increase the wear of the co-operating compressor connected to said evaporator.
Another object of the present invention is thus to decrease the wear of the
compressor connected to the evaporator by minimising the liquid content of the
evaporated medium leaving the evaporator.

A particular problem relating to heat exchangers of the plate type is that
15 accumulated liquid medium in the lower parts of the evaporator will cause non-
uniform streaming with a decreased efficiency as a result. One object with the
present invention is thus to improve the efficiency of a heat exchanger of the plate
type by minimising the amount of accumulated liquid medium in the evaporator.

Another problem regarding heat exchangers is that the
20 superheater/supercooler is an external unit, making the heat exchangers bulky and
not very cost efficient. Still a further object of the present invention is thus to
provide a heat exchanger of the plate type with an integrated
supercooler/superheater.

With reference to figure 2, the working principle for an evaporator according
25 to the present invention will now be described. A medium, e.g. a coolant medium
such as freon, circulates from an evaporation chamber 110' to a compressor 120' and
further to a condenser 130' and finally back into the evaporation chamber 110' via
an expansion valve 140', in fig. 2. According to the invention, the evaporation
chamber 110' is equipped with drainage means 160' in its lower parts allowing
30 accumulated medium in a liquid state to be piloted in an external feedback loop. This
will decrease the liquid level 150' in the evaporation chamber and therefore increase
the efficiency of the evaporator as well as decreasing the amount of liquid arriving at
compressor 120', and as a consequence decrease the wear of the compressor 120', as
understood by a person skilled in the art. The drainage means consist of a connection
35 e.g. by a hose, pipe or tube between an additional outlet 410' in the lower parts of
the evaporation chamber 110' and an additional inlet 170' in an expansion means,
such as an expansion valve 140', in a preferred embodiment. The expansion means
may also be a capillary tube or the like. The expansion valve 140' is equipped with
an additional inlet 170' for the feedback drainage in the preferred embodiment. The

additional inlet 170' in the expansion valve 140' experience a negative pressure producing an injector effect caused by the medium streaming through the expansion valve 140' from condenser 130' to evaporator 110' at a relatively high velocity. This injector effect can be exploited to transport the liquid medium from outlet 410' back into expansion valve 140'.

In an alternative embodiment, the drainage means does not lead back into the expansion valve 140' but into the connection between expansion valve 140' and evaporation chamber 110', as indicated by arrow 180' in fig. 2.

In another embodiment, said external loop leads back directly into said evaporation chamber 110', illustrated by arrow 190' in fig. 2.

In yet a further embodiment, said drainage means 160' comprise a pump.

Injector effects as described above may also be exploited in these alternative embodiments. This means that an expansion driven injector will be used to transport the medium through the drainage means according to the invention.

The evaporator, condenser and heat exchanger according to the present invention shall now be described in more detail for the specific case that the evaporator and condenser are realised in form of a heat exchanger of the plate type. Plate type heat exchangers are generally known devices for heat exchange between different media and are used in a multitude of contexts and the present invention is not limited to any special application. However, the invention is most easily applied to plate type heat exchangers of the wholly brazed type. This means that the heat exchanger consists of plates having a groove pattern and inlet and outlet connections for the media. The plates are placed in a package and are brazed together into a fixed unit. Separate ducts are thus formed for the media, typically circulating in opposite directions between alternate pairs of plates. This technique is commonly known and will not be described in detail here.

For illustrative purposes only, the invention will here be described for the particular case with a heat exchanger in which heat exchange takes place between three media, I, II and III but the invention is applicable for heat exchange between an arbitrary number of media. The media used could for instance be: I=freon, II=brine and III=water, but other alternatives exist as known to a person skilled in the art.

Referring now to figure 3, a front side A' of a plate 300 of a heat exchanger of the plate type according to the present invention is depicted. The plate in fig. 3 is illustrated in its correct operational standing position, i.e. the force of gravity is working downwards in fig. 3. The A' side is equipped with an inlet 305 and outlet 310 for the II medium together with an inlet 315 and outlet 320 for medium I. A barrier D separates the media from each other so that medium II will circulate to the left hand side of barrier D and medium I to the right hand side of barrier D in fig. 3, i.e. in the condenser chamber 380. According to the invention, a further barrier E is

provided which forms a delimited zone A'' together with a channel C'', between said zone A'' and the condenser chamber 380 in which medium I circulates. The barriers are obtained by a suitable, interactive, groove- and recess pattern between the plates as known, e.g. from the document WO00/03189 and will not be described in detail here.

Referring now to fig. 4, the rear side, B', of the plate 300 in fig. 3 is illustrated in its correct operational standing position. The B' side have inlets 405 and 420 together with outlets 415 and 425 and a barrier F which separates the media from each other so that medium I will circulate to the left, in the evaporation chamber 450, and medium III to the right, of barrier F in fig 4. In addition, the invention provides an outlet 410 in the lower parts of evaporation chamber 450, connected to the external drainage means 430, according to the present invention. The drainage means 430 have the identical function as the drainage means 160' described above with reference to fig. 2, and can be realised in the same way. Thus, the drainage means 430 consist of a connection e.g. by a hose, pipe or tube between outlet 410 and expansion valve 440, illustrated by arrow 460 in fig. 4, or, alternatively, between the outlet 410 and somewhere between expansion valve 440 and inlet 405, illustrated by arrow 470 in fig. 4, or, alternatively, between outlet 410 and an additional inlet 490, illustrated by arrow 480 in fig 4. The drainage means can exploit the injector effect described above, i.e. comprise an expansion driven injector, and may possibly also comprise a pump, as explained above with reference to fig.2. The drainage according to the present invention thus automatically drains liquid from the evaporation chamber 450. During operation, this drainage thus continuously drains a relatively small amount of liquid from the evaporation chamber and then injects it back into the chamber. When the heat exchanger is turned off, or stops for some reason, liquid will accumulate in the evaporation chamber 450 as a result. However, the drainage according to the present invention efficiently drains the evaporation chamber 450 as soon as the heat exchanger is turned on. Thus, immediately after starting the heat exchanger, there will be a relatively large amount of liquid draining through the drainage, however, the amount of draining liquid will decrease rather fast. This drainage increases the efficiency of the evaporator and the heat exchanger and decreases the wear of the compressor, as a person skilled in the art realises.

Now, with reference to fig. 3 and 4, the working principle for the heat exchanger according to the present invention will be described. For purely illustrative purposes, a heat exchanger applied for a heat pump application will be described. Medium II, e.g. brine, enters at inlet 305 in fig 3 at a relatively higher temperature, e.g. corresponding to the ground temperature, e.g. at 12° C, and is piloted downwards in a duct chamber 385 under heat exchange with medium I, and

thereafter leaves through outlet 310 at a lower temperature, e.g. 7°, to be piloted back to the ground in a closed loop.

Inlet 315 is fed with medium I, e.g. freon, by compressor so that medium I enters into condenser chamber 380 through inlet 315 under high pressure and high temperature, e.g. 80° C. Medium I is piloted towards the inlet 370 of the channel C'' under heat exchange with medium III and further up through the channel C'' and piloted through the delimited zone A'' under heat exchange with itself. Thus, the zone A'' according to the present invention provides a double effect in that it works as a superheater during the evaporation stage of medium I and as a supercooler during the condensing stage of medium I. Thus, medium I is further condensed in the delimited zone A''. This increases the efficiency of the heat exchanger and reduces the wear of the compressor, as a person skilled in the art will understand.

The medium I leaves outlet 320 at a lower temperature, e.g. 32° C, and is thereafter fed to expansion valve 440. After passing the expansion valve 440, medium I enters through inlet 405 at a considerable lower pressure and temperature, e.g. 2° C. The medium I starts to evaporate at a lower pressure and evaporates further when heated in evaporation chamber 450. Medium I is then piloted towards the delimited zone B'' under heat exchange with medium II, to exit through outlet 415. When arriving at the delimited zone B'', the temperature of medium I in this illustrative example will be around 7° C. Medium I has a heat exchange with itself in the delimited zone B'', as described above, and is thus in this stage, i.e. the evaporation stage, subject for above described superheater function. The superheater ensures that all liquid evaporates before arriving to the compressor, which will further increase the efficiency of the heat exchanger and reduce the wear of the compressor, as a person skilled in the art realises.

Furthermore, accumulated medium I in form of liquid will be fed back by the drainage means 430 according to the present invention, as described above. Medium I will thereafter be directed from outlet 415, at a higher temperature, e.g. 10° C, to the compressor in a closed loop.

Thus, medium I circulates in a closed loop from evaporation chamber 450 to the compressor and further to the condenser chamber 380 and thereafter back to the evaporation chamber 450 through expansion valve 440. Medium I can also circulate in the feedback loop formed by the drainage outlet 410 and the drainage means 430 according to the present invention, described above.

Medium III, e.g. water, enters through inlet 420 at a relatively lower temperature, e.g. 38° C, and leaves outlet 425 at a relatively higher temperature, e.g. 44° C, since medium III has heat exchange with medium I in the heat exchanger. Medium III enters into a duct chamber 485 through an inlet 420 at a relatively low temperature, e.g. 38° C, and is piloted through said duct chamber 485 under heat

exchange with said medium I. Said medium III then leaves said duct chamber 485 through an outlet 425 at a relatively higher temperature, e.g. 44° III. Thus, as a net effect, medium II has given a certain amount of heat to medium III.

Although the present invention has been described in the case for an
5 evaporator and condenser in a heat exchanger of the plate type used for a heat pump application, it shall be understood that the invention is applicable in a wide variety of heating and/or cooling applications. For instance, a person skilled in the art realises that above described process can realise an air condition application, the heat exchanger need not be of a plate type etc. Furthermore, the evaporator according to
10 the invention can be used not only in heat exchangers but is applicable in any evaporating process. Figures 3 and 4 are not to scale and illustrate merely the working principle of the invention by way of example. Therefore, a person skilled in the art can realise the invention in many different ways without departing from the scope of the present invention as defined by the following claims.

ALBIHNSA MALMÖ AB

CLAIMS

1. An evaporator comprising an evaporation chamber (110') having at least one inlet and at least one outlet allowing a medium to enter into, and exit from, said chamber, characterised in that said evaporation chamber (110') is equipped with an external loop (160') adapted to drain said medium from the lower parts of said evaporation chamber (110') and introduce said medium back into the evaporation chamber (110').
2. An evaporator according to claim 1, characterised in that said inlet is connected to an expansion means (140') by connection means, said expansion means (140') being equipped with an additional inlet (170'), and that said external loop (160') is arranged to introduce said medium back into the evaporation chamber (110') through the additional inlet (170') of said expansion means (140').
3. An evaporator according to claim 1, characterised in that said inlet is equipped with an additional inlet (170'), and that said external loop (160') is arranged to introduce said medium back into the evaporation chamber (110') through said additional inlet (170') by means of an expansion driven injector.
4. An evaporator according to claim 1, characterised in that said external loop (160') comprises a pump.
5. A heat exchanger characterised in that it comprises an evaporator according to any of claims 1-4.
6. A heat exchanger of the plate type formed of interacting alternating plates having a groove pattern forming at least two separate duct loop systems allowing a first medium (I) to circulate in the first of said duct systems under heat exchange with a second medium (II) circulating in the second of said duct systems, wherein said first duct loop system comprises a part forming an evaporation chamber (450) having at least one inlet (405) and at least one outlet (415) allowing said medium (I) to enter into, and exit from, said chamber (450), characterised in that said evaporation chamber (450) is equipped with an additional outlet (410) connected to drainage means (430) adapted to drain said medium (I) from said evaporation chamber's (450) lower parts in an external loop and introduce said medium (I) back into said evaporation chamber (450).

7. A heat exchanger according to claim 6, characterised in that said interacting plates form a third duct system in which a third medium (III) can circulate under heat exchange with at least said first medium (I).
8. A heat exchanger according to claim 7, characterised in that said chamber (450) has a delimited zone (B''), defined, and, that the outlet (415) of said chamber (450) is connected, via a compressor, to a part of said first duct system forming a condenser chamber (380) having a substantially vertical channel (C'') piloting medium (I) from said chamber's (380) lower parts up into a delimited defined zone (A''), wherein said medium (I) can circulate in said zones (A'') and (B'') under heat exchange with itself.
9. A heat exchanger according to claim 8, further characterised in that it comprises:
 - a duct chamber (385) having an inlet (305) and outlet (310) allowing said medium (II) to enter said duct chamber (385) through said inlet (305) to be piloted through said duct chamber (385) under heat exchange with said medium (I), and to leave said duct chamber (385) through said outlet (310),
 - an evaporation chamber (450) having an inlet (405), an outlet (415) and a delimited zone (B''), allowing said medium (I) to enter through said inlet (405) to be piloted through said evaporation chamber (450) under heat exchange with said medium (II) and further through said zone (B'') under heat exchange with itself, and to leave said evaporation chamber (450) through an outlet (415), and,
 - a compressor and a condenser chamber (380) having an inlet (315) and an outlet (320), said condenser chamber (380) further having a delimited zone (A'') and a substantially vertical channel (C'') leading to said delimited zone (A'') from said condenser chamber's (380) lower parts and said compressor being connected to said outlet (415) and said inlet (315), allowing said medium (I) to be piloted from said outlet (415) into said condenser chamber (380) through said inlet (315) via said compressor and further piloted through said condenser chamber (380) under heat exchange with said medium (III), and further piloted up through said channel (C'') into and through said zone (A'') through which said medium (I) is allowed to be piloted under heat exchange with itself and thereafter to leave said condenser chamber (380) through said outlet (320), and,
 - an expansion valve (440) connected to said outlet (320) and inlet (405) allowing said medium (I) to be piloted from said condenser chamber (380) into said evaporation chamber (450) through said inlet (405) via said expansion valve (440), and,

- 5 - a duct chamber (485) having an inlet (420) and an outlet (425) allowing said medium (III) to enter into said duct chamber (485) through said inlet (420) and to be piloted through said duct chamber (485) under heat exchange with said medium (I) and allowing said medium (III) to leave said duct chamber (485) through said outlet (425).
- 10 10. A heat exchanger according to any of claims 6-9, characterised in that said drainage means (430) are arranged to introduce said medium (I) back into the evaporation chamber (450) through an external expansion means (440) feeding said inlet (405) with medium (I).
- 10 11. A heat exchanger according to any of claims 6-9, characterised in that said drainage means are arranged to introduce said medium (I) in an additional inlet by means of an expansion driven injector.
12. A heat exchanger according to any of claims 6-10, characterised in that said drainage means (430) comprise a pump.
- 15 13. A heat pump system characterised in that it comprises an evaporator according to claims 1-4 and/or a heat exchanger according to claims 5-12.
14. An air condition system characterised in that it comprises an evaporator according to claims 1-4 and/or a heat exchanger according to claims 5-12.

46 40 6119689

Ink. t. Patent- och reg.verket

2003-04-17

Huvudfaxen Kassin

11

ABSTRACT

The present invention relates generally to an evaporator and more specifically to an evaporator having an evaporating chamber (110') equipped with drainage means (160'). The drainage means (160') drain accumulated liquid from the evaporator's lower parts and include an external expansion driven injector and/or an external pump. The evaporator according to the invention can be used e.g. in a heat exchanger, e.g. in a heat pump system or air condition system, and said vacuum driven injector can be integrated with an expansion means (140') of the heat exchanger. The invention also relates to a condenser to be used together with said evaporator in a heat exchanger of the plate type realising an integrated superheater/supercooler. This is accomplished by the definition and use of delimited interacting zones through which the cooling medium circulates under heat exchange with itself.

(fig. 2)

Ink. t. Patent- och r.g.verket

2003-04-17

Huvudfaxen Kassan




Fig. 1

Ink. t. Patent- och reg.verket

2003-04-17

Huvudfoxen Kassan




Fig. 2

Ink. t. Patent- och registerverket

2003-04-17

Huvudfaxen Kassan




Fig. 4

Fig. 3

This Page is inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ BLACK BORDERS
- ☒ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☐ BLURED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☒ COLORED OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REPERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images
problems checked, please do not report the
problems to the IFW Image Problem Mailbox**